


N-type TOPCon HIGH PERFORMANCE BIFACIAL MODULE

PB108-11-490-515



The module picture is for reference only

490-515 _{Wp}

Power Output Range

23.2 %

Maximum Efficiency

0~+3 %

Positive power tolerance

1500 _{VDC}

Maximum System Voltage

KEY FEATURES


-  Perfect for rooftop scenario application
-  Excellent power generation
-  Excellent anti-LID & anti-PID performance
-  Excellent temperature coefficient (Pmax): -0.29%/°C
-  Excellent weak-light performance
-  Excellent warranty assurance




LINEAR PERFORMANCE WARRANTY

15 years Product Warranty / 30 years Linear Power Warranty



0.4% Annual Degradation over 30 years



Dimensions of PV Module



*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.



PACKAGING CONFIGURATION

	40ft(HQ)	20ft
Number of modules per container	864	180
Number of modules per pallet	36	36
Number of pallets per container	24	5
Packaging box dimensions (LxWxH) in mm	1985×1110×1260	
Box gross weight[kg]	1022	

ELECTRICAL DATA (STC)

Model Type	PB108-11-490-515					
Rated Power in Watts-Pmax(Wp)	490	495	500	505	510	515
Open Circuit Voltage-Voc(V)	39.61	39.81	40.02	40.22	40.42	40.62
Short Circuit Current-Isc(A)	15.74	15.81	15.88	15.95	16.02	16.08
Maximum Power Voltage-Vmpp(V)	32.65	32.85	33.05	33.25	33.45	33.64
Maximum Power Current-Impp(A)	15.01	15.07	15.13	15.19	15.25	15.31
Module Efficiency (%) *	22.0	22.3	22.5	22.7	22.9	23.2

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

Bifacial factor: 80±5(%) * Module Efficiency (%): Rounding to the nearest number

ELECTRICAL DATA (BNPI)

Model Type	PB108-11-490-515					
Maximum Power-Pmax (Wp)	543	548	554	560	565	571
Open Circuit Voltage-Voc (V)	39.61	39.81	40.02	40.22	40.42	40.62
Short Circuit Current-Isc (A)	17.44	17.52	17.60	17.67	17.75	17.82
Maximum Power Voltage-Vmpp (V)	32.65	32.85	33.05	33.25	33.45	33.64
Maximum Power Current-Impp (A)	16.63	16.70	16.76	16.83	16.89	16.96

BNPI: Front side irradiance 1000 W/m², Rear side irradiance 135 W/m², Cell Temperature 25°C, Air Mass AM1.5.

Power measurement tolerance: ±3%

Electrical characteristics with 10% rear side power gain

Total Equivalent power -Pmax (Wp)	539	545	550	556	561	567
Open Circuit Voltage-Voc(V)	39.61	39.81	40.02	40.22	40.42	40.62
Short Circuit Current-Isc(A)	17.31	17.39	17.47	17.55	17.62	17.69
Maximum Power Voltage-Vmpp(V)	32.65	32.85	33.05	33.25	33.45	33.64
Maximum Power Current-Impp(A)	16.51	16.58	16.64	16.71	16.78	16.84

Rear side power gain: The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

MECHANICAL DATA

Solar cells	N-type TOPCon
Cell configuration	108cells (6×9+6×9)
Module dimensions	1961×1134×30mm (77.20×44.65×1.18 in)
Weight	27kg (59.52 lb)
Superstrate	2.0mm(0.08 in), High Transmission, AR Coated Heat Strengthened Glass
Substrate	2.0mm(0.08 in), Heat Strengthened Glass
Frame	Anodized Aluminium Alloy, Black
J-Box	Potted, IP68, 1500VDC, 3 Schottky by pass diodes
Cables	4.0mm ² , 1400mm(55.12 in) (+), 1400mm(55.12 in) (-), connector included, or customized length
Connector	MC4 EVO2/PV-SY02/Others
Maximum mechanical test load	5400 Pa (front) / 2400 Pa (back), under certain installation method

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	0.046%/°C
Temperature Coefficient of Pmax	-0.29%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	35A
Limiting Reverse Current	35A



TIANJIN PALMBRI INDUSTRY & TRADE Co.,Ltd.

No. 1988 of Yingbin Avenue, Free trade Zone of Tianjin (CBD), 300450, Tianjin, China

+86 153 2010 1753

info@palmבריenergy.com

info@palmברי.com

www.palmבריenergy.com

© 2026 TIANJIN PALMBRI INDUSTRY & TRADE Co.,Ltd. All rights reserved