


N-type TOPCon HIGH PERFORMANCE BIFACIAL MODULE

PB132-11-610-635



The module picture is for reference only

610-635 _{Wp}

Power Output Range

23.5 %

Maximum Efficiency

0~+3 %

Positive power tolerance

1500 _{VDC}

Maximum System Voltage

KEY FEATURES



Excellent power generation



Excellent anti-LID & anti-PID performance



Excellent temperature coefficient (Pmax): - 0.29%/°C



Excellent weak-light performance




Excellent warranty assurance




LINEAR PERFORMANCE WARRANTY

15 years Product Warranty / 30 years Linear Power Warranty

0.4% Annual Degradation over 30 years



Dimensions of PV Module Unit: mm



*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

ELECTRICAL DATA (STC)

Model Type	PB132-11-610-635					
Rated Power in Watts-Pmax(Wp)	610	615	620	625	630	635
Open Circuit Voltage-Voc(V)	48.69	48.89	49.08	49.27	49.46	49.65
Short Circuit Current-Isc(A)	15.92	15.98	16.04	16.10	16.16	16.22
Maximum Power Voltage-Vmpp(V)	40.46	40.64	40.81	40.98	41.17	41.36
Maximum Power Current-Impp(A)	15.08	15.14	15.20	15.26	15.31	15.36
Module Efficiency (%) *	22.6	22.8	23.0	23.1	23.3	23.5

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

Bifacial factor: 80±5(%) * Module Efficiency (%): Rounding to the nearest number

ELECTRICAL DATA (BNPI)

Model Type	PB132-11-610-635					
Maximum Power-Pmax (Wp)	676	681	687	693	698	704
Open Circuit Voltage-Voc (V)	48.69	48.89	49.08	49.27	49.46	49.65
Short Circuit Current-Isc (A)	17.64	17.71	17.77	17.84	17.91	17.97
Maximum Power Voltage-Vmpp (V)	40.46	40.64	40.81	40.98	41.17	41.36
Maximum Power Current-Impp (A)	16.70	16.77	16.83	16.90	16.96	17.01

BNPI: Front side irradiance 1000 W/m², Rear side irradiance 135 W/m², Cell Temperature 25°C, Air Mass AM1.5.

Power measurement tolerance: ±3%

Electrical characteristics with 10% rear side power gain

Total Equivalent power -Pmax (Wp)	671	677	682	688	693	699
Open Circuit Voltage-Voc(V)	48.69	48.89	49.08	49.27	49.46	49.65
Short Circuit Current-Isc(A)	17.51	17.58	17.64	17.71	17.78	17.84
Maximum Power Voltage-Vmpp(V)	40.46	40.64	40.81	40.98	41.17	41.36
Maximum Power Current-Impp(A)	16.59	16.65	16.72	16.79	16.84	16.90

Rear side power gain: The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.


MECHANICAL DATA

Solar cells	N-type TOPCon
Cell configuration	132 cells (6×11+6×11)
Module dimensions	2382×1134×30mm (93.78×44.65×1.18 in)
Weight	32.5kg (71.65 lb)
Superstrate	2.0mm(0.08 in), High Transmission, AR Coated Heat Strengthened Glass
Substrate	2.0mm(0.08 in), Heat Strengthened Glass
Frame	Anodized Aluminium Alloy, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky by pass diodes
Cables	4.0mm ² , 350mm(13.78 in) (+), 230mm(9.06 in) (-), connector included, or customized length
Connector	PV-SY02/Others
Maximum mechanical test load	5400 Pa (front) / 2400 Pa (back), under certain installation method


TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	0.046%/°C
Temperature Coefficient of Pmax	-0.29%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	35A
Limiting Reverse Current	35A

I-V characteristics at different irradiancies



I-V characteristics at different temperatures



PACKAGING CONFIGURATION

	40ft(HQ)	20ft
Number of modules per container	720	144
Number of modules per pallet	36	36
Number of pallets per container	20	4
Packaging box dimensions (LxWxH) in mm	2395×1110×1260	
Box gross weight[kg]	1238	



TIANJIN PALMBRI INDUSTRY & TRADE Co.,Ltd.

No. 1988 of Yingbin Avenue, Free trade Zone of Tianjin (CBD), 300450, Tianjin, China

+86 153 2010 1753

info@palmbrienergy.com

info@palmbri.com

www.palmbrienergy.com

© 2026 TIANJIN PALMBRI INDUSTRY & TRADE Co.,Ltd. All rights reserved